BANHAM

SECURITY

CHANGING ROUTER FOR APP PANELS

- Please press D and enter your master manager code. "SET DATE & TIME?" will appear
- Press NO until you get to "WI-FI SETUP?"
- Then press YES and "SETUP WITH WI-FI DEVICE?" will appear
- Press NO and "SSID?" will appear
- Press YES

If the old SSID is on screen, you will need to remove details by pressing the felt arrow and press the **C** button, then repeat the process until all text has been removed.

• Then enter the new SSID details

For upper case characters select the letter then press the **A** button and it will change to upper case. Symbols are found by pressing the 1 button. Press the numbers on the keypad to select the first letter of the username, providing the first letter is correct press right arrow button for the next cursor position.

- Press YES and "SSID?" will appear
- Press NO and "Password?" will appear
- Press YES and enter the new wi-fi password. (using the same process as above)
- Press **YES** & then press **NO**. Signal Strength will appear along with the strength number. This means the system is now connected to the wi-fi.
- Press NO and "WI-FI SETUP?" will appear
- Press A button, "Please Wait Saving NVM Data" will appear

The system will go back to the home screen.

Please now contact the **Alarm Receiving Centre (ARC)** on **020 7622 5151** to confirm signals are being received.

If you have any questions or queries, please contact Banham Technical Support during office working hours on 020 7622 5151 or email Tech@Banham.com

Banham Patent Locks Limited | Reg. No: 457812 | England



CHANGING ROUTER USING A SMARTPHONE/PC

- Please press **D** and enter your Master Manager code. "**SET DATE & TIME?**" will appear
- Press NO until you get to "WI-FI SETUP?"
- Then press YES and "Setup with Wi-Fi Device?" will appear
- Press YES and Are You Sure? will appear
- Press YES and the panel will display its SSID and password

Example: Pyronix - ABCD2468


Pwd: ABCD2468

- On your smartphone or PC go to your network settings (Wifi) and connect to your alarm panel (example ABCD2468) and then open a web browser on your device
- Type into your web browser 192.168.0.1 and a list of available networks will appear like below:



• Select the router that you wish the alarm panel to connect to, enter the router password and then select the 'tick' button

The SSID / password should not have a space at the beginning or end and should not exceed 32 characters in length.





The panel will start connecting to the selected router and the below page will be displayed. Once the
panel has connected to the selected router the following message will appear on the alarm panel
keypad. "Connected to Network"



You can now exit from the managers menu by pressing NO button until you get to "WI-FI SETUP?" and
then press the A button. Once you have exited from the master manager menu you can also close the
browser on your Smartphone/PC

Please now contact the **Alarm Receiving Centre (ARC)** on **020 7622 5151** to confirm signals are being received.

If you have any questions or queries, please contact Banham Technical Support during office working hours on 020 7622 5151 or email <u>Tech@Banham.com</u>